



PI-10

STAINLESS STEEL CONSTRUCTION

TECHNICAL SPECIFICATIONS

Hourly production: 200 Kg / 240 Kg
 Load capacity per programme: 10 Kg
 Timer (min-max): 0' - 6'
 Single Phase: 550 W
 Three phase: 370 W

External dimensions

· Width: 433 mm
 · Depth: 635 mm
 · Height: 625 mm

external dimensions with support

· height with support: 433 mm
 · depth with support: 638 mm
 · height with support: 1040 mm

Net weight: 39 Kg

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose.
- Auto-drag of waste to the drain.
- Energy optimisation thanks to engine optimization.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- Timer 0-6min and continuous operation.

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stand
- Filter with no-foam feature.



ER-0437/1/96
 UNE-EN ISO 9001
 SAMMIC, S.L. (Sociedad Unipersonal)
 Basarte, 1 - 20720 AZKOITIA - www.sammic.com

