



PI-20

STAINLESS STEEL CONSTRUCTION

- Side stirrers covered with silicon carbide abrasive (approved by NSF).
- ° Aluminium base plate lined with silicon carbide abrasive (approved by NSF)

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- ° Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose.
- Auto-drag of waste to the drain.
- Energy optimisation thanks to engine optimization.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- Timer 0-6min and continuous operation.

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stand.
- Filter with no-foam feature.

TECHNICAL SPECIFICATIONS

Hourly production: 400 Kg / 480 Kg
Load capacity per programme: 20 Kg
Timer (min-max): 0' - 6'
Loading: 550 W

External dimensions

·Width: 433 mm
·Depth: 635 mm
·Height: 735 mm

external dimensions with support

·height with support: 433 mm
·depth with support: 638 mm
·height with support: 1155 mm

Net weight: 39 Kg



ER-0437/1/96
UNE-EN ISO 9001
SAMMIC, S.L. (Sociedad Unipersonal)
Basarte, 1 - 20720 AZKOITIA - www.sammic.com

