



Electrolux

Modular Cooking Range Line 900XP Electric Bratt Pan 80lt with mild steel bottom

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux



Modular Cooking Range Line

900XP Electric Bratt Pan 80lt with mild
steel bottom

391143 (E9BREHMOF0)

900XP Electric Bratt Pan – 80
liter with mild steel bottom

Short Form Specification

Item No. _____

Infrared heating elements positioned under the cooking surface. Polished mild steel plated cooking surface for roasting, browning, stewing, preparation of sauces, sautéing, boiling and braising. To be installed on stainless steel feet with height adjustment up to 50 mm and can be installed on cantilever systems. Includes mechanism to manually tilt the pan and double-skinned lid in stainless steel. Cooking temperature can be set through thermostat and the energy input through an energy regulator.

Exterior panels of unit in stainless steel with Scotch Brite finish. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Double-skin well and lid to reduce heat dispersion.
- Infrared heating elements mounted below the cooking surface.
- Lid is double-lined, insulated in 20/10 Stainless steel.
- IPX5 water resistance certification.
- Actual cooking temperature setting through adjustable thermostat.
- Working temperature can be set from 120 °C to 300 °C.
- Energy input controlled by energy regulator.
- Heat-insulated: limited heat radiation and low energy consumption.
- Manual tilting mechanism to facilitate pan emptying.
- Smooth large surfaces, easy access for cleaning.
- The special design of the control knob system guarantees against water infiltration.
- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.

Construction

- Cooking surface in mild steel for sautéing, poaching, steaming, boiling, stewing and regular frying.
- All pan internal surfaces round and polished.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

- 4 wheels, 2 swivelling with brake (700/900XP). It is mandatory to install with base supports for feet/wheels. ☐ PNC 206135
- Flanged feet kit ☐ PNC 206136
- Frontal kicking strip, 800mm (not for refr-freezer base) ☐ PNC 206176
- Frontal kicking strip, 1000mm (not for refr-freezer base) ☐ PNC 206177
- Frontal kicking strip, 1200mm (not for refr-freezer base) ☐ PNC 206178
- Frontal kicking strip, 1600mm (not for refr-freezer base) ☐ PNC 206179
- Pair of side kicking strips (not for refr-freezer base) ☐ PNC 206180

APPROVAL: _____



Electrolux

Modular Cooking Range Line 900XP Electric Bratt Pan 80lt with mild steel bottom

- 2 panels for service duct for single installation PNC 206181 ☐
- 2 panels for service duct for back to back installation PNC 206202 ☐
- Chimney upstand, 800mm PNC 206304 ☐
- Base support for feet or wheels - 800mm (700/900) PNC 206367 ☐



**Modular Cooking Range Line
900XP Electric Bratt Pan 80lt with mild steel bottom**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2012.09.28



Modular Cooking Range Line
900XP Electric Bratt Pan 80lt
with mild steel bottom

Technical drawing of the EQ 6000 machine showing dimensions in inches and millimeters:

- Top width: 15 5/16" (389 mm)
- Internal top width: 13 3/8" (340 mm)
- Total height: 6 15/16" (176 mm)
- Height from base to top panel: 2 13/16" (71 mm)
- Base width segments: 2 3/16" (55 mm) on each side
- Distance between base feet: 27 3/16" (690 mm)
- Right-side mounting bracket offset: 0 9/16" (14 mm)
- Labels: EI, WI, EQ

[illegible]

CWI = Cold Water inlet
EI = Electrical connection

[illegible]

Supply voltage:

391143 (E9BREHMOF0)

400 V/3N ph/50/60 Hz

Total Watts:

13 kW

Key Information:

Cooking Surface Depth:	565 mm
-------------------------------	--------

Cooking Surface Width: 680 mm

Cooking Well Height: 130 mm

Well Capacity, Max: 80 lt

Working Temperature MIN: 120 °C

Working Temperature MAX: 300 °C

Net weight: 150 kg

Shipping weight: 170 kg

Shipping height: 1040 mm

Shipping width: 1020 mm

Shipping depth: 860 mm

Shipping volume: 0.91 m³

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Modular Cooking Range Line
900XP Electric Bratt Pan 80lt with mild steel bottom

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

