

## **ECOMAX G404 GLASSWASHER**





The fast and reliable glasswasher in compact design. Perfect for start-ups, small bars or restaurants.

Glasswasher ecomax G404		
Cycle times*	60 / 120 sec.	
Capacity per hour*	up to 60 racks	
Wash/rinse temperature	approx 55° C / approx 60° C	
Tank capacity	10 I	
Fresh water consumption/rack	2.0	
Wash pump	0.18 kW	
Heating booster/tank	1.9 kW	
Total loading	2.1 kW	
Rated voltage	240 /50/1 - 15A	
Width/Depth/Height	436/534/700 mm	
Loading height	308 mm	
Rack size	400x 390 mm	


\* hot water connection \*\*with 400/50/3
The installation of machines with integrated water softener requires a back-flow safety device (at site) according to DVGW-DIN 1988.
Required supply pressure: with integral rinse pressure pump: 0.8 to 6 bar; without integral rinse pressure pump: 2 to 6 bar


## **PRODUCT ADVANTAGES**

- Electronic control with digital temperature indication
- Flat surface of control panel
- 2 selectable wash cycles
- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- Indented nozzles prevent blocking
- Thermostop-function for guaranteed temperatures
- Integrated self-cleaning cycle
- Removal of rinse arms without any tools
- USB connection for easier service access
- Easy access to all parts
- Deep drawn rack track
- Door safety lock
- Double-walled insulated front door
- Integrated cycle counting, e.g. for control of water treatment system

## STANDARD EQUIPMENT

- Glass rack with 4 sloped rows 139321-57
- Cutlery basket CB1
- Heater with thermostat control
- Electric cable, flexible water supply hose and drain hose
- Rear panelling





CONNECTIONS	
① Drain hose	2,000 mm   ID20/OD25
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	3.0 -6 bar (300- 600 kPa)
Max. supply water temperature	60 °C
3 Power cord	2,000 mm
Supply hose for	
4 Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

